

Zep Manufacturing

ZEP FREEZE

ISSUE DATE: 03/16/95
 SUPERSEDES: 01/31/95
 ZEP FREEZE
 PRODUCT NO.: 0240
 Aerosol Gum Remover
 MANUFACTURER: ZEP MANUFACTURING COMPANY
 P.O. BOX 2015
 ATLANTA, GEORGIA 30301

HMIS CODES:
 HEALTH: 1
 FLAM.: 0
 REACT.: 1
 PERS. PROTECT.: B
 CHRONIC HAZ.: No

FIRST AID PROCEDURES:
 SKIN: Wash contaminated skin thoroughly with soap or a mild detergent. Apply a skin cream with lanolin. Get medical attention if irritation persists.
 EYES: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting upper and lower lids. Get medical attention at once.
 INHALE: Move exposed person to fresh air. If breathing has stopped, perform artificial respiration. Get medical attention immediately.
 INGEST: This route of exposure is not likely due to product nature.

 SECTION I - EMERGENCY CONTACTS

TELEPHONE: (404) 352-1680 Between 8:00 AM - 5:00 PM (EST)
 MEDICAL EMERGENCY:
 (770) 439-4200
 (770) 432-2873
 (770) 424-4789
 (770) 424-2048
 (770) 455-8160
 (770) 552-8836
 Non Office Hours, Weekends, And Holidays, Please Call Local Poison Control.
 TRANSPORTATION EMERGENCY: (770) 922-0923
 CHEMTREC:
 (800) 424-9300 Toll Free - Calls Recorded
 DISTRICT OF COLUMBIA:
 (202) 483-7616 All Calls Recorded

 SECTION II - HAZARDOUS INGREDIENTS

DESIGNATIONS	(PPM)	EFFECTS (SEE NOTICE)	% IN PROD.
1,1,1,2- TETRAFLUOROETHANE hfc-134a CAS#: 811-97-2 RTECS#: None OSHA PEL: 1000 ppm	1000	CNS	>90

 SECTION III - HEALTH HAZARD DATA

SPECIAL NOTE: MSDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under recommended conditions of use (diluted) so long as prescribed safety precautions are practiced.
 ACUTE EFFECTS OF OVEREXPOSURE: Intentional misuse or deliberate inhalation of high concentrations of vapor is harmful and may cause heart irregularities, unconsciousness, or death. Prolonged contact with liquid can cause frostbite.
 CHRONIC EFFECTS OF OVEREXPOSURE: There are no known effects from chronic exposure to this product. None of the hazardous ingredients are listed as carcinogens by IARC, NTP, or OSHA.
 EST'D PEL/TLV: Not established
 PRIMARY ROUTES OF ENTRY: Inh, Skin.

 SECTION IV - SPECIAL PROTECTION INFORMATION

PROTECTIVE CLOTHING: The use of neoprene, nitrile or natural rubber gloves is strongly recommended, especially for prolonged contact.
 EYE PROTECTION: Wear tight-fitting safety glasses when using or handling this product.
 RESPIRATORY PROTECTION: If ventilation is adequate, wear a properly fitting MSHA or OSHA-approved respirator.
 VENTILATION: Ventilation should be equal to outdoors. Use exhaust fans and/or exhaust hood in enclosed spaces.

 SECTION V - PHYSICAL DATA

BOILING POINT (F): -15
 VAPOR PRESSURE (mmHg): 96 psi
 VAPOR DENSITY (AIR = 1): 6.06
 SOLUBILITY IN WATER: Negligible
 SPECIFIC GRAVITY: N/A
 EVAPORATION RATE (N/D = 1): N/D
 pH (CONCENTRATE): N/A
 pH (USE DILUTION OF N/A): N/A
 VOC CONTENT (CONCENTRATE): 0.0%
 APPEARANCE AND ODOR: A clear, colorless liquid with a faint ether-like odor.

 SECTION VI - FIRE AND EXPLOSION DATA

FLASH POINT (C) (METHOD USED): Nonflammable (CSMA)
 FLAMMABLE LIMITS:
 LEL: N/A
 UEL: N/A
 EXTINGUISHING MEDIA: Carbon dioxide, dry chemical and foam.
 SPECIAL FIRE FIGHTING: Wear self-contained positive pres. breathing apparatus.
 UNUSUAL FIRE HAZARDS: Direct water onto intact containers to prevent bursting.

 SECTION VII - REACTIVITY DATA

STABILITY: Stable
 INCOMPATIBILITY (AVOID): None
 POLYMERIZATION: Will not occur.
 HAZARDOUS DECOMPOSITION: Hydrogen fluoride and hydrogen gas.

Zep Manufacturing

ZEP FREEZE

SECTION VIII - SPILL AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Observe safety precautions in sections 4 & 9 during clean-up. Large spills are unlikely due to packaging. Spill may be absorbed on an inert absorbent material (eg Zep-0-Zorb), and placed in a suitable container for disposal. Wash area thoroughly with a detergent solution and rinse well with water.

WASTE DISPOSAL METHOD: Product is consumed in use. Do not crush, puncture or incinerate spent containers. Large numbers of aerosol containers may require handling as a hazardous waste, but in most states total hazardous waste quantities less than 220 lbs per month may allow disposal in a chemical or industrial waste landfill. Consult local, state and federal agencies for the proper disposal method in your area.

RCRA HAZ. WASTE NOS.: N/A

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN WHEN HANDLING AND STORING:

Concentration of spray on skin or eyes can quickly cause frostbite and may result in permanent injury. Keep product out of eyes. Vapors are heavier than air and will accumulate at low points. Ventilation should include floor level exhausting. Do not store at temperatures above 120 deg F (39 deg C) or in direct sunlight. Do not puncture or incinerate container. Keep out of the reach of children.

SECTION X - REGULATORY INFORMATION

DOT PROPER SHIPPING NAME: Liquefied Gas, N.O.S.
(Tetrafluoroethane)

NOTE: DOT information applies to larger package sizes of affected products. For some products, DOT may require alternate names and labeling in accordance with packaging group requirements.

DOT HAZARD CLASS: 2.2

DOT PACKING GROUP:

DOT I.D. NUMBER: UN1956

DOT LABEL/PLACARD: Non Fl Gas

EPA TSCA CHEMICAL INVENTORY: All ingredients are listed

EPA CWA 40CFR PART 117 SUBSTANCE (RQ IN A SINGLE CONTAINER): None

NOTICE

Thank you for your interest in, and use of, Zep products. Zep Manufacturing Co. is pleased to be of service to you by supplying this Material Safety Data Sheet for your files. Zep Manufacturing is concerned for your health and safety. Zep products can be used safely with proper protective equipment and proper handling practices consistent with label instructions and the MSDS. Before using any Zep product, be sure to read the complete label and the Material Safety Data Sheet.

As a further word of caution, Zep wishes to advise that serious accidents have resulted from the misuse of "emptied" containers. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, or other sources of ignition; they may explode or develop harmful vapors and possibly cause injury or death. Clean empty containers by triple rinsing with water or an appropriate solvent. Empty containers must be sent to a drum reconitioner before reuse.

TERMS AND ABBREVIATIONS LISTED ALPHABETICALLY BY SECTION:

SECTION II: HAZARDOUS INGREDIENTS

CAR: Carcinogen - A chemical listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC) or OSHA as a definite or possible human cancer causing agent.

CAS#: Chemical Abstract Services Registry Number - A universally accepted numbering system for chemical substances.

CBL: Combustible - At temperatures between 100 deg F and 200 deg F chemical gives off enough vapor to ignite if a source of ignition is present as tested with a closed cup tester.

CNS: Central Nervous System depressant which reduces the activity of the brain and spinal cord.

COR: Corrosive - Causes irreversible injury to living tissue (e.g. burns).

DESIGNATIONS: Chemical and common names of hazardous ingredients.

EIR: Eye Irritant Only - Causes reversible reddening and/or inflammation of eye tissues.

EXPOSURE LIMITS: The time weighted average (TWA) airborne concentration at which most workers can be exposed without any expected adverse effects. Primary sources include ACGIH TLV's, and OSHA PEL's (TWA, STEL and ceiling limits).

ACGIH: American Conference of Government Industrial Hygienists.

CEILING: The concentration that should not be exceeded in the workplace during any part of the working exposure.

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limit - A set of time weighted average exposure values, established by OSHA, for a normal 8-hour day of a 40-hour work week.

PPM: Parts per million - unit of measure for exposure limits.

(S) SKIN: Skin contact with substance can contribute to overall exposure.

STEL: Short Term Exposure Limit - Maximum concentration for a continuous 15-minute exposure period.

TLV: Threshold Limit Value - A set of time weighted average exposure limits, established by the ACGIH, for a normal 8-hour day of a 40-hour work week.

FBL: Flammable - At temperatures under 100 deg F, chemical gives off enough vapor to ignite if a source of ignition is present as tested with a closed cup tester.

HAZARDOUS INGREDIENTS: Chemical substances determined to be potential health or physical hazards based on the criteria established in the OSHA Hazard Communication Standard - 29 CFR 1910.1200

HTX: Highly toxic - the probable lethal dose for a 70 kg (150 lb.) man and may be approximated as less than 6 teaspoons (2 tablespoons)

IRR: Irritant - Causes reversible effects in living tissues (e.g. inflammation) - primarily skin and eyes.

N/A: Not Applicable - Category is not appropriate for this product.

N/D: Not Determined - Insufficient information to make a determination for this item.

RTECS#: Registry of Toxic Effects of Chemical Substances - an unreviewed listing of published toxicology data on chemical substances.

SARA: Superfund Amendments and Reauthorization Act - Section 313 designates chemicals for possible reporting for the Toxics Release Inventory.

SEN: Sensitizer - Causes allergic reaction after repeated exposure.

TOX: Toxic - The probable lethal dose for a 70 kg (150 lb.) man is one ounce (2 tablespoons) or more.
(rev. 1/98)

Zep Manufacturing

ZEP FREEZE

SECTION III: HEALTH HAZARD DATA

ACUTE EFFECT: An adverse effect on the human body from a single exposure with symptoms developing almost immediately after exposure or within a relatively short time.

CHRONIC EFFECT: Adverse effects that are most likely to occur from repeated exposure over a long period of time.

EST'D PEL/TLV: This estimated, time-weighted-average, exposure limit, developed by using a formula provided by the ACGIH, pertains to airborne concentrations from the product as a whole. This value should serve as guide for providing safe workplace conditions to nearly all workers.

HMIS CODES: Hazardous Material Identification System - a rating system developed by the National Paint and Coating Association for estimating the hazard potential of a chemical under normal workplace conditions. These risk estimates are indicated by a numerical rating given in each of three hazard areas (Health/Flammability/Reactivity) ranging from a low of zero to a high of 4. The presence of a chronic hazard is indicated with a yes. Consult HMIS training guides for Personal Protection letter codes which indicate necessary protective equipment.

PRIMARY ROUTE OF ENTRY: The way one or more hazardous ingredients may enter the body and cause a generalized-systemic or specific-organ toxic effect.

ING: Ingestion - A primary route of exposure through swallowing of material.

INH: Inhalation - A primary route of exposure through breathing of vapors.

SKIN: A primary route of exposure through contact with the skin.

SECTION IV: SPECIAL PROTECTION INFORMATION

Where respiratory protection is recommended, use only MSHA and NIOSH approved respirators and dust masks.

MSHA: Mine Safety and Health Administration

NIOSH: National Institute for Occupational Safety and Health.

SECTION V: PHYSICAL DATA

EVAPORATION RATE: Refers to the rate of change from the liquid state to the vapor state at ambient temperature and pressure in comparison to a given substance (e.g. water).

pH: A value representing the acidity or alkalinity of an aqueous solution (Acidic pH = 1; Neutral pH = 7; Alkaline pH = 14)

VOC CONTENT: The percentage or amount in pounds per gallon of the product that is regulated as a Volatile Organic Compound under the Clean Air Act of 1990 and various state jurisdictions.

SOLUBILITY IN WATER: A description of the ability of the product to dissolve in water.

SECTION VII: REACTIVITY DATA

HAZARDOUS DECOMPOSITION: Breakdown products expected to be produced upon product decomposition by extreme heat or fire.

INCOMPATIBILITY: Material contact by extreme heat and the conditions to avoid to prevent hazardous reactions.

POLYMERIZATION: Indicates the tendency of the product's molecules to combine with themselves in a chemical reaction, releasing excess pressure and heat.

STABILITY: Indicates the susceptibility of the product to spontaneously and dangerously decompose.

SECTION VIII: SPILL AND DISPOSAL PROCEDURES

RCRA WASTE NOS: RCRA (Resource Conservation and Recovery Act) waste codes (40 CFR 261) applicable to the disposal of spilled or unusable product from the original container.

SECTION X: TRANSPORTATION DATA

CWA: Clean Water Act - Federal Law which regulates chemical releases to bodies of water.

RQ: Reportable Quantity - The amount of the specific ingredient that, when spilled to the ground and can enter a storm sewer or natural watershed, must be reported to the National Response Center, and other regulatory agencies.

TSCA: Toxic Substances Control Act - a federal law requiring all commercial chemical substances to appear on an inventory maintained by the EPA.

DISCLAIMER: All statements, technical information and recommendations contained herein are based on available scientific tests or data which we believe to be reliable. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. Zep assumes no liability or responsibility for loss or damage resulting from the improper use or handling of our products, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the product's label and Material Safety Data Sheet.
(rev. 1/98)

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES: although preparer and owner have taken reasonable care in the preparation of this document, we extend no warranties and make no representation as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each user should make a determination as to the suitability of the information for their particular purpose(s). A request has been made to the manufacturer to approve the contents of this material safety data sheet. Upon receipt of any changes a new MSDS will be made available.

COMPAS Code: 22610510