

	Page: 1
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil

™ Trademark, Valvoline or its subsidiaries, regisred in various countries

Relevant identified uses of the substance or mixture and uses advised against

Details of the supplier of the safety data sheet Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL	Emergency telephone number 1-800-VALVOLINE Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS label elements

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	Not a hazardous substance or mixture.	5.2547
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	1.1945
Phosphorodithioic acid, mixed	113706-15-3	Skin Irrit. 2; H315	1.036

	Page: 2
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

O,O-bis(sec-Bu and isooctyl) esters, zinc salts		Eye Dam. 1; H318	
---	--	------------------	--

SECTION 4. FIRST AID MEASURES

General advice	: No hazards which require special first aid measures.
If inhaled	: If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities. Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways)
Notes to physician	: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

	Page: 3
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
 Nitrogen oxides (NOx)
 Sulphur oxides
 hydrogen sulfide
 mercaptans
 zinc oxide
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.

	Page: 4
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.
------------	---------

Engineering measures : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear resistant gloves (consult your safety equipment supplier).
Wear as appropriate:
Safety shoes

Hygiene measures : General industrial hygiene practice.

	Page: 5
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: amber
Odour	: hydrocarbon-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: > 424.9 °F / 218.3 °C
Flash point	: > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 6 %(V) Calculated Explosive Limit
Lower explosion limit	: 1 %(V) Calculated Explosive Limit
Vapour pressure	: 0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.880 g/cm3 (15.56 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 115 mm2/s (40 °C)

	Page: 6
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Acids
Strong oxidizing agents
water

Hazardous decomposition products : carbon dioxide and carbon monoxide
Hydrocarbons
hydrogen sulfide
Nitrogen oxides (NOx)
Sulphur oxides
zinc oxide
mercaptans

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Acute oral toxicity : LD50 (Rat): 2,900 mg/kg

Remarks: Information given is based on data obtained from similar substances.

	Page: 7
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
 Assessment: Not classified as acutely toxic by dermal absorption under GHS.
 Remarks: Information given is based on data obtained from similar substances.

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Result: Corrosive

Remarks: Information given is based on data obtained from similar substances.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Genotoxicity in vitro : Remarks: In vitro tests showed mutagenic effects which were not observed with in vivo test.

	Page: 8
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

Genotoxicity in vivo : Test Type: chromosome aberration assay
 Test species: Mouse
 Cell type: peripheral blood cells
 Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Effects on fertility : Species: Rat
 Application Route: Oral
 Dose: 100 mg/kg bw/day
 Symptoms: No effects on reproduction parameters

Effects on foetal development : Species: Rat
 Application Route: Oral
 Developmental Toxicity: No observed adverse effect level F1:
 100 mg/kg body weight

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

	Page: 9
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.5 mg/l

Exposure time: 96 h

Remarks: Information given is based on data obtained from similar substances.

Persistence and degradability

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Biodegradability : Result: Not readily biodegradable.

Remarks: Information given is based on data obtained from similar substances.

No data available

Bioaccumulative potential

Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts:

Bioaccumulation : Bioconcentration factor (BCF): 3

Remarks: Information given is based on data obtained from similar substances.

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

		Page: 10
SAFETY DATA SHEET		Revision Date: 09/23/2016
		Print Date: 11/1/2016
		SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780		Version: 1.4

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG ROAD_C

Not dangerous goods

TDG RAIL_C

Not dangerous goods

TDG INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

	Page: 11
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : No SARA Hazards

SARA 313

Phosphorodithioic acid, 113706-15-3 1.03 %
 mixed O,O-bis(sec-Bu and
 isooctyl) esters, zinc salts

California Prop 65 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION


Further information

Revision Date: 09/23/2016

NFPA:	HMIS III:
--------------	------------------

	Page: 12
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

Flammability



Health

Instability

Special hazard.

HEALTH	0
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

NFPA Flammable and Combustible Liquids Classification
 Combustible Liquid Class IIIB

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

	Page: 13
SAFETY DATA SHEET	Revision Date: 09/23/2016
	Print Date: 11/1/2016
	SDS Number: R0306034
Premium Blue™ Heavy Duty Diesel SAE 15W-40 Engine Oil ™ Trademark, Valvoline or its subsidiaries, regisred in various countries 773780	Version: 1.4

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
 WHMIS : Workplace Hazardous Materials Information System