Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 USA **Telephone: 1-87-Permatex** (877) 376-2839

Emergency: 800-255-3924

Baldorsan

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name:

SENSOR SAFE ULTRA GREY RTV 3.5 OZ

Item No: **Product Type:** 82194 Silicone

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	40-50	Not Listed	Not Listed
CALCIUM CARBONATE 471-34-1	20-30	10 mg/m³ total dust	15 mg/m³ dust; 5 mg/m³ respir
GARNET MINERAL 1302-62-1	20-30	Not Listed	Not Listed
VINYL OXIMINOSILANE 2224-33-1	1-10	Not Listed	Not Listed
SILICA, AMORPHOUS TREATED 68909-20-6	1-10	10 mg/m³ inhal; 3 mg/m³ respir	20 mppcf
STEARIC ACID 57-11-4	1-10	Not Listed	Not Listed
2-BUTANONE OXIME 96-29-7	***	Not Listed	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity:

Note: This product does not contain microcyrstalline silica. May cause eye and skin irritation. ****When this product if exposed to moisture, butanone oxime may be formed. When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors.

Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde. May be harmful if swallowed. May irritate lips, gums, tongue, mouth, nose and throat.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.

Signs and Symptoms of Exposure: Butanone oxime produced during curing is toxic and irritates eyes, nose and throat. Overexposure to

the silane may cause coma and respiratory failure.

Medical Conditions Recognized as None known Being Aggravated by Exposure:

4. FIRST AID MEASURES

Ingestion: Inhalation:

Rinse mouth If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention. Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact:

Wipe off paste with paper towel or cloth. Wash off with soap and water If skin irritation persists, call a

physician

Eye Contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Hazardous Products Formed by Fire or Thermal

Flash Point (°F/C):

Decomposition:

Recommended Extinguishing Media: Special Fire-Fighting Procedures:

Unusual Fire/Explosion Hazards:

More than 200 degrees F. Method: Tag Closed Cup Carbon Dioxide, Dry Chemicals, Foam,

Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime.

Silica fume, Oxides of carbon. Formaldehyde,

None

Lower Explosive Limit: **Upper Explosive Limit:**

Not determined Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Handling: Store in a dry area below 90 degrees F. Keep container closed when not in use. Avoid contact with skin and eyes. Do not wear contact lenses. Do not inhale vapors.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses.

Skin:

rubber or plastic gloves

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure

limits during the use of this product.

Respiratory Protection:

Not required under normal use. An approved respirator (i.e. NIOSH, etc.) should be worn when

exposures are expected to exceed the applicable limits...

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Grey paste

Odor:

MILD

Boiling Point (°F):

Not applicable, polymeric material

Does not apply

Solubility in Water: Specific Gravity:

Polymerized

VOC Content(Wt.%):

1.5 7.1% by weight

Vapor Pressure:

Less than 5 mm Hg @ 70 degrees F.

Vapor Density (Air=1):

Not determined

Evaporation Rate:

Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability:

Hazardous Polymerization:

Incompatabilities:

Conditions to Avoid:

Hazardous Products Formed by Fire or Thermal

Decomposition:

Stable at normal conditions

Will not occur

Polymerized by contact with moisture. Strong oxidizers. Acids, Iron.

Exposure to moisture

Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime.

Silica fume, Oxides of carbon. Formaldehyde,

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number:

NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name:

Unrestricted

Hazard Class: **UN/ID Number:** NONE None

Marine Pollutant:

None

Proper Shipping Name:

not regulated

Class or Division: **UN/NA Number:**

None None

IMDG

Proper Shipping:

Unrestricted

Hazard Class: UN Number:

None None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

SARA 313 Information

NONE

CALIFORNIA PROP 65:

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating:

HEALTH 1, FLAMMABILITY 1, INSTABILITY 1

Estimated HMIS Classification:

HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:

Denise Boyd, Health and Safety Manager

Revision Date: 02/15/2005

Company:

Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA

Revision

Number:

06106

Telephone Number: 1-87-Permatex (877) 376-2839